

G60 Handheld Thermography Camera



The thermographic handheld camera is based on the thermal technology, specially designed for the needs of temperature measuring applications. People can quickly troubleshoot faults on-site.

Key Features


- Thermal resolution: 640 x 512 (327 680 pixels)
- NETD : < 35 mK (@ 25 °C,F#=1.0)
- Temperature measurement range : -20 °C to 650 °C (-4 °F to 1202 °F)
- Accuracy: Max ($\pm 2^{\circ}\text{C}/3.6^{\circ}\text{F}$, $\pm 2\%$)
- Measurement Presets: Center spot, Hot spot, Cold spot, User Preset Point/Line/Area
- Auto/Manual/Laser focus
- 50 Hz image frequency
- 4.3" LCD touch screen display
- 8MP Optical camera
- Up to 4 hours continuous running

Specification

| Thermal Module | |
|---------------------------------|--|
| Image Sensor | Vanadium Oxide Uncooled Focal Plane Arrays |
| IR Resolution | 640 x 512 (327 680 pixels) |
| Pixel Pitch | 17 μ m |
| Spectral Range | 8 - 14 μ m |
| NETD | < 35 mK (@25°C), F#=1.0 |
| Focal Length | 25 mm |
| FOV (Field of View) | 25° x 19° |
| Image Frequency | 50 Hz |
| Focus | Continuous Autofocus/Autofocus/Manual Focus/Laser Assisted Focus |
| IFOV (Spatial Resolution) | 0.68 mrad |
| Aperture | F1.1 |
| Minimum Focus Distance | 0.3 m (0.98 ft) |
| Optical Module | |
| Picture Resolution | Configurable: 2 MP, 5 MP, 8 MP |
| Video Resolution | 640 x 480 |
| Focus | Fixed |
| FOV | 25° x 19° |
| Image Display | |
| Display | 800 x 480 Resolution, 4.3" LCD Touch Screen |
| Color Palettes | White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain |
| Digital Zoom | 1x, 2x, 4x, 8x |
| Image Modes | Thermal/Optical/Fusion/PIP |
| PIP | Thermal Picture in Optical Picture |
| Fusion | Thermal Picture and Optical Picture Combined |
| Measurement and Analysis | |
| Object Temperature Range | -20 °C to 650 °C (-4 °F to 1202 °F) |
| Accuracy | Max ($\pm 2^{\circ}\text{C}/3.6^{\circ}\text{F}$, $\pm 2\%$) |
| Measurement Presets | Center Spot, Hot Spot, Cold Spot, Off |
| Point | 10 User Presets |
| Line | 1 User Preset |
| Area | 3 User Presets |
| High Temperature Alarm | Audible Warning |
| Color Alarm (Isotherm) | Above/Below/Interval/Insulation |
| Storage | |
| Storage Media | Removable Micro SD Card (64 GB) |
| Image Storage Capacity | 60 000 Images |
| Image File Format | JPEG with Measurement Data Included |
| Video Storage Capacity | 54 Hours |

| | |
|---------------------------|--|
| Video File Format | MP4 |
| Functions | |
| Laser Pointer | Yes |
| Laser Distance Meter | Yes |
| Laser Type | Class II |
| Wi-Fi | 802.11 b/g/n (2.4 GHz) |
| Bluetooth | Bluetooth 4.2 |
| Level/Span | Auto/Manual |
| Text Comment | Max 200 Characters |
| Voice Comment | Max 60 Seconds |
| UVC Cast Screen | Yes |
| Power System | |
| Power Supply | 12 V DC/1.5A, 5V DC/2A (Charging via USB) |
| Power Consumption | 5 W |
| Battery Type | Dismountable and Rechargeable Li-ion Battery |
| Battery Operating Time | 4 Hours Continuous Running |
| General | |
| Menu Language | 17 Languages English, Russian, Hungarian, German, Italian, Czech, Slovak, French, Polish, Portuguese, Spanish, Romanian, Danish, Turkish, Korean, Traditional Chinese, Japanese |
| Working Temperature Range | -20 °C to 50 °C (-4 °F to 122 °F) |
| Storage Temperature Range | -20 °C to 60 °C (-4 °F to 140 °F) |
| Protection level | IP54 |
| Drop Test Height | 2 m (6.56 ft) |
| Interface | USB Type-C |
| Weight | Approx. 1000 g (2.20 lb) |
| Dimension | 284.7 mm × 118.3 mm × 127.1 mm (11.21 " × 4.66 " × 5.00 ") |
| Tripod Mounting | UNC ¼"-20 |

Packing List



Optional



Available model

HM-TP76-25SVF/W-G60

Dimension

