DIGITAL MICRO-VICKERS HARDNESS TESTER CODE ISH-TDV1000A**







- Measure hardness of thin or small workpieces
- Based on Vickers (HV), can be converted to Rockwell (HRA, HRB and HRC)
- According to ISO 6507







slice holder (included)

SPECIFICATION

Test force	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1kgf	
Vickers scales	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1	
Stage elevation	manual	
Load control	automatic (load/dwell/unload)	
Load dwell time	5~60 second (5 second increment)	
Objective	10X, 40X	
Eyepiece	15X	
Total magnification	150X (for observation) 600X (for measurement)	
Max. workpiece height	85mm	
Max. testing width	85mm (from the center of indenter to the wall of main body)	
X-Y stage	dimensions: 100×100mm	
	travel range: 25×25mm	
	graduation: 0.01mm	
Data output	RS232C	
Power supply	110/220V, 50Hz **	
Dimension	540x500x640mm	
Weight	50kg	

STANDARD DELIVERY

Main unit	1 pc
10X, 40X objective	1 pc of each
Micro Vickers indenter	1 pc
Hardness test block 400~500HV0.2	1 pc
Hardness test block 700~800HV1	1 pc
Slice holder	1 pc
Vice	1 pc
Cylinder holder	1 pc
Level	1 pc
Anti-dust cover	1 pc

OPTIONAL ACCESSORY

20X objective	ISH-TDV-20X	
Hardness test block 400~500HV0.2	HDT-B-HV02C	
Hardness test block 700~750HV1	HDT-B-HV1F	
Measuring system	9631-130	
Camera adapter	ISH-TDV-ADAPTER	

^{***}Add "-**B**" on code No. when power supply is 110/220V, 60Hz